



EuroTouch-2IN System

Mas de Garrigues - 81170 Loubers

Tèl : + 33 (0)5 63 53 92 14 - Fax : + 33 (0)5 63 53 94 25

Administratif-fbasse@wanadoo.fr


Agence Toulouse EuroTouch-Centre Technique 2IN System

9 Chemin de Lourmet - 31180 Castelmaurou

Ligne IP : 0877 821 335 (Tarification Locale) Tèl/Fax : +33 (0)5 61 35 84 30

www.2in-system.com - contact@2in-system.com

Fiche Technique CI5-TTL



FEATURES

Supports Intel 430TX PCIset
Socket 7, 75~300MHz CPU Speed
2 SIMMs for up to 128MB DRAM
C&T 65550 VGA for CRT/LCD display
Hardware Monitoring
PC/104, COMI/2 Ports
Watchdog Timer

SPECIFICATIONS

Processor Socket

PGA Socket 7, 90MHz to 300MHz

Processor

Intel (P54C, P55C/MMX), Cyrix (6x86, 6x86L, 6x86MX), AMD (K5, K6)

Chipset: Intel 82430TX PCIset

System Memory

Two 72-pin SIMM sockets Max. 128MB, FPM/EDO DRAM

L2 Cache: 512KB Pipelined Burst SRAM

BIOS

Y2K compliant Award BIOS

Supports DMI & Plug and Play 2M-bit Flash ROM

Power Management

APM 1.2 (ACPI via ATX power supply)

Multi-I/O

SMC 37C669

COM1:RS-232 with 16 byte FIFO COM2:RS-232 or RS-422/485 (jumper selectable)

Parallel Port

1xhigh speed Bi-directional SPP/ECP/EPP

IDE Interface

2 x Bus Mastering EIDE mode 4, up to 4 devices, Ultra DMA/33

FDD Interface

2x360K/720K/1.2MB/1.44MB/2.88MB FDDs

Onboard VGA

C&T 65550 chip with 1MB memory (2MB optional)

Supports LCD, TFT & CRT display

AT Power Supply Connector

6-pin external power connector

ATX Power Supply Connector

6-pin header

Hardware Monitoring

Intel LM75 monitoring CPU temperature, Intel LM78 monitoring system temperature, voltages and fan speeds System Monitor utility bundled,Optional Intel LDCM software

Speaker

Internal buzzer and external speaker connector

Watchdog Timer : 16 levels

PC/104 Extension : 16 bit, 104 pins ATX

Power Supply Connector

For 5VSB control signal link to passive backplane

Keyboard

PS/2 keyboard DIN connector and external connector

Mouse

Pin header for PS/2 mouse connector

Other Features

Switching voltage regulator

Form Factor

Half size, 6-layer PCB

Dimensions 18.5cm x 12.2cm (7.4" x 4.8")

Operating Temperature 0oC~60oC

Humidity 5%~95%

Ordering Information

CI5TTL Half-size Socket 7 430TX with C&T 65550 CRT/ LCD VGA interface with 1MB RAM (2MB optional)

CI5TTLD Half-size Socket 7 430TX with C&T 65550 CRT/LCD VGA interface and LM78

CI5TTLW Half-size Socket 7 430TX without C&T 65550 CRT/LGA interface and LM78