

2INEM-817RX / 2INEM-1617RX



- Easy installation
- Compact and ergonomically
- Integrated 8/16 Port KVM



1U 17" LCD-Monitor Keyboard-Drawer with
integrated 8 Port KVM (2INEM-817RX)
or 16 Port KVM (2INEM-1617RX)

- 1U Drawercase 530mm deep
- RoHS conform
- Integrated Teleskope-Rails
- integrated 8/16 Port KVM

Features:

- Various mounting slides for any 1U (19") Rack
- integrated Teleskope-Rails
- Front panel lockable with practical knurled screws
- RGB analog LCD Display up to 1280x1024 with 300 cd/m (sq) brightness (17")

Specification:

Casing:

- RoHS conform
- Heavy-duty Steel
- Casecolor RAL 9005
- Adjustable Rack-Slides for convenient positioning of the unit when in use
- Connections 2INEM-817RX: 8xDB-15 (PS/2 and VGA), Flash Port
- Connections 2INEM-1617RX: 16xDB-15 (PS/2 and VGA), Flash Port
- 106 Key Windows PS/2 Keyboard with Touchpad
- Monitor open angle 0° - 105°
- Keyboard Layouts: german / us-english / french / italian and spanish (further Layouts on request)

2INEM-817RX



2INEM-1617RX



Technical Specification LCD Monitor

Display Size:	17"
Resolution:	Maximum 1280x1024
Number of colors::	16,2 M.
Optical frequenz:	H: 30,0KHz – 70,0KHz V: 55,0KHz – 75,0KHz
Viewing angle:	H: 140° / V: 130°
Bandwidth:	80MHz
Brightness:	300 cd/m ²
Contrast Ratio:	700:1
Response time:	8ms
Pixel pitch:	0,264mm(H) x 0,264mm(V)
Backlights:	4xCCFL
Power Supply:	Input: 100V – 240V AC, 48Hz – 62HZ Output: DC 12V, 4,0A

Technical Specification KVM-Switch

Computer connections:	8	16
Daisy-Chain:	64 (with 8 Port modules)	128 (with 16 Port modules)
Port selection:	OSD / Hot Key / Push Buttons	
Connectors on the backside:	8xDB-15 (PS/2 + VGA), Daisy-Chain IN/OUT, Flash-Port	16xDB-15 (PS/2 + VGA), Daisy-Chain IN/OUT, Flash-Port
Resolution:	Max. 1280x1024	
Flash upgrade port:	Firmware upgradeable Via Mini DIN 6 Pin console Mouse Port	
Available Cable length:	1,8m (KAB-102) / 3,0m (KAB-103) / 5,0m (KAB-105)	
Power Supply:	DC 5V, 2,5A	
Support:	Standard PS/2 Connectors for PC	