

Corat-1701 / Corat-1716



- Easy installation
- compact and ergonomically
- PS/2 Connector on the front side to connect an external Mouse



1U 17" LCD-Monitor Keyboard-Drawer with Dual-Rail Slides and 16 Port CAT5 KVM-Switch (Corat-1716) optionally

- 1U Drawercase
- RoHS conform
- Dual-Rail Slide
- Optional 16 Port CAT5 KVM (Corat-1716)

Features:

- Dual-Rail sliding console for any 1U (19") system rack
- Flexible External Mouse
- Monitor and Keyboard worked separately
- RGB analog LCD-Display up to 1280x1024 with 300cd/m² brightness
- Supports Microsoft Intellimouse, Logitech FirstMouse+, MouseMan+, and others
- Supports Windows , NetWare , Linux and Free BSD

Specifications:

Casing:

- RoHS conform
- Heavy-duty Steel
- Casecolor Pantone 10C Cool Gray
- Dual-Rail design has LCD-Display and Keyboard worked separately
- Adjustable Rack-Slides for convenient positioning of the unit when in use
- 106 Key PS/2 Keyboard with Touchpad
- Monitor open angle 0° - 105°
- Connection: 1xVGA / 2x PS/2 (Corat-1701), 16xRJ45 (Corat-1716)
- Keyboard Layouts: german, us-english, french, italian and spanish



Corat-1701



Corat-1716



Technical Specification LCD Monitor

| | |
|-------------------|--|
| Display Size: | 17" |
| Resolution: | Maximum 1280x1024 |
| Number of colors: | 16,2 M. |
| Optical frequenz: | H: 30KHz – 70KHz V: 55KHz – 75KHz |
| Viewing angle: | H: 140° / V: 130° |
| Bandwidth: | 80MHz |
| Brightness: | 300 cd/m ² |
| Contrast Ratio: | 700:1 |
| Response time: | 8ms |
| Pixel pitch: | 0,264mm(H) x 0,264mm(V) |
| Backlights: | CCFL |
| Power Supply: | Input: 100V – 240V AC, 48Hz – 62Hz Output: DC 12V, 4,2A |

Technical Specification CAT5 KVM-Switch (Corat-1716)

| | |
|-----------------------------|--|
| Computer connections: | 16 Direct |
| Daisy-Chain: | 256 max. |
| Port selection: | OSD / Hot Key / Push Buttons |
| Connectors on the backside: | 16 x RJ45 (embedded), Daisy-Chain IN/OUT, Flash-Port |
| Resolution: | Max. 1280x1024 |
| Flash upgrade port: | Firmware upgradeable Via Mini DIN 6 Pin console Mouse Port |
| Adapter Available Distance: | 30m (in connection with PS/2 or USB Dongles optional available) |
| Power Supply: | DC 12V, 4,2A |
| Support: | All PS/2 Connectors are PC spezified, USB Connectors are spezified for PC, SUN and MAC |

Dimension and Weight

| | | | |
|------------|-----------|--------------------------------------|---------|
| Corat-1701 | Unpacked: | 584,2 x 444,5 x 44,45 mm (W x L x H) | 14,1 kg |
| | Packing: | 685,8 x 787,4 x 228,6 mm (W x L x H) | 18,6 kg |
| Corat-1716 | Unpacked: | 584,2 x 444,5 x 44,45 mm (W x L x H) | 15,0 kg |
| | Packing: | 685,8 x 787,4 x 228,6 mm (W x L x H) | 19,5 kg |